

mc 0,35
ft³ 12.4



kg 8,8
lb 19.4

EN: Armchair with solid oak frame with upholstery on seat, sides and backrest

IT: Poltrona con struttura in massello di rovere con imbottiture presenti sul sedile, fianchi e schienale
DE: Sessel mit Gestell aus massivem Eichenholz, gepolstert auf Sitz, Seiten und Rückenlehne
FR: Fauteuil avec structure en chêne massif avec revêtement de l'assise, des côtés et du dossier
ES: Sillón con estructura de roble macizo con tapicería en el asiento, los laterales y el respaldo

MATERIALS

Materiali
Materialien
Matériaux
Materiales

• SEAT - SEDUTA - SITZ - ASSISE - ASIENTO

EN: Seat upholstered with flexible polyurethane foam (density 63 kg/m³), flame retardant (class 1 IM), birch plywood inner structure, fabric cover

IT: Sedile imbottito con poliuretano espanso flessibile (densità 63 kg/m³), ignifugo (classe 1 IM), struttura interna in multistrato di betulla, rivestito in tessuto

DE: Sitz gepolstert mit flexiblem Polyurethanschaum (Dichte 63 kg/m³), schwer entflammbar (Klasse 1 IM), Innenstruktur aus Birkenperrholz, mit Stoff bezogen

FR: Assise garnie de mousse de polyuréthane souple (densité 63 kg/m³), ignifugée (classe 1 IM), structure interne en contreplaqué de bouleau, recouverte de tissu

ES: Asiento tapizado con espuma de poliuretano flexible (densidad 63 kg/m³), ignífugo (clase 1 IM), estructura interior de madera contrachapada de abedul, cubierta de tela

FABRIC - TESSUTO - STOFF - TISSU - TEJIDO

Cat. A - C (excluding C36+C39) - D120+D123 - G - H - P

EN: For more information see finishing legend on the website

IT: Per maggiori informazioni vedere legenda finiture sul sito web

• FRAME - TELAIO - STRUKTUR - STRUCTURE - ARMAZÓN

EN: Solid oak

IT: In massello di rovere

DE: Eiche massiv

FR: Chêne massif

ES: Roble macizo

EN: Wooden parts have jointed components

IT: Le parti in legno presentano componenti giuntati

FINISH - FINITURA - AUSFÜHRUNG - FINITIONS - ACABADO

EN: Water-based paint, matt finish (5 gloss), anti-scratch

IT: Verniciatura a base acqua, finitura opaca (5 gloss), antigraffio

DE: Lack auf Wasserbasis, Ausführung matt (5 gloss), kratzfest

FR: Peinture à base d'eau, finition mate (5 gloss), anti-rayures

ES: Pintura a base de agua, acabado mate (brillo 5), anti-arañazos




EN: Lacquered visible grains

IT: Laccato poro aperto

DE: Laqué pore ouvert

FR: Offenporig lackiert

ES: Lacado poro abierto



FEET - PIEDINI - GLEITER - PATINS - TACOS

EN: Felt, suitable for delicate and sensitive floors (wood, ceramics, marble)
IT: Feltro, adatti per pavimenti delicati e sensibili (legno, ceramica, marmo)
DE: Filz, für sanfte und zartfühlende Boden geeignet (Holz, Keramik, Marmor)
FR: Feutre incurvé, pour sols délicats et sensibles (bois, marbre, céramique)
ES: Fieltro curvado, aptos para pisos delicados y sensibles (madera, cerámica, mármol)

REGULATIONS AND CERTIFICATES

Normative e Certificazioni
Bestimmungen und Zertifikat
Normatives et certifications
Normativas y certificados

• ENVIRONMENTAL IMPACT - IMPATTO AMBIENTALE - UMWELTBELASTUNG - IMPACT DUR L'ENVIRONNEMENT - IMPACTO AMBIENTAL

| MATERIAL Materiale | Kg WEIGHT Peso | % TOTAL ITEM Totale articolo | MATERIAL RECYCLABILITY Riciclabilità del materiale | % MINIMUM RECYCLED AT ORIGIN Minima riciclato all'origine | % RECYCLABLE END OF PRODUCT LIFE Riciclabile fine vita prodotto |
|--|----------------------|---------------------------------------|---|--|---|
| Steel Acciaio | 0,0046 | 0,05 | YES | 33,2 | 100 |
| Polyurethane foam Poliuretano espanso | 2 | 22,5 | NO | 0 | 0 |
| Solid wood Legno massello | 4,7 | 54 | YES | 0 | 100 |
| Plywood Multistrato | 1,6 | 19 | YES | 0 | 100 |
| Fabric Tessuto | 0,39 | 4,13 | NO | 0 | 0 |
| Felt Feltro | 0,0016 | 0,02 | NO | 0 | 0 |
| TOTAL TOTALE | 8,8 Kg | -- | -- | -- | 73,2 % |

• COMPANY CERTIFICATIONS - CERTIFICAZIONI AZIENDALI - UNTERNEHMENSZERTIFIZIERUNGEN - CERTIFICATIONS D'ENTREPRISE - CERTIFICACIONES DE LA EMPRESA

ISO 14001
Environmental management system
Sistema di gestione ambientale

ISO 9001
Quality management system
Sistema di gestione della qualità

